CHAIN-GE IS COMING TO ROTARY GATE SYSYTEMS!

MODEL SL-CD VEHICULAR CHAIN DRIVE OPERATOR



UL325 MONITORED OBSTRUCTION INPUTS TO PREVENT ENTRAPMENT OR GATE CLOSING ON PEOPLE/PROPERTY



BUILT IN BATTERY BACKUP LONG
USE AFTER POWER FAILURE*

NUMBER OF CYCLES AND TIME OF USE ON BATTERY POWER DEPENDS ON MANY FACTORS, INCLUDING SIZE AND WEIGHT OF GATE, ACCESSORIES, ETC.



CONVENIENT, LOCKABLE MANUAL
RELEASE FOR MULTIPLE OPEN
OPTIONS IF YOU LOSE POWER



- MOUNTING POINTS ARE THE SAME AS THE POPULAR SL-RD RACK AND PINION SLIDE GATE OPERATOR
- CONVENIENT LOCKING MANUAL RELEASE FOR OPENING, NEVER GET LOCKED IN OR OUT OF YOUR PROPERTY
- INDUSTRY STANDARD #40 CHAIN
- 3D PRINTED REVERSIBLE CHAIN GUARD FOR EASE OF USE ON SITE
- PERMANENT MAGNET DC MOTOR FOR PROVIDES AMPLE TORQUE FOR ANY APPLICATION



MECHANICAL

BODY: BILLET ALUMINUM, POWDER-COATED FOR ADDITIONAL CORROSION RESISTANCE

CHAIN GUARD: 3D PRINTED PET-G FOR HEAT AND UV RESISTANCE

SPEED: APPROXIMATELY 12"/SEC

CHAIN: UNIT IS SHIPPED WITH 20FT (6M) OF #40 ROLLER CHAIN

ELECTRICAL

AUTOMATIC LIMIT LEARNING AND SOFT START/STOP TUNING

AUTO-CLOSE TIMER 1-99 SEC

BUILT IN ON/OFF SWITCH

BUILT IN ALARM AND RESET SWITCH

PROGRAMMING THROUGH DISPLAY

PARTIAL-OPEN AND ANTI-TAILGATING FEATURES

115VAC OUTLET AVAILABLE FOR ACCESSORIES

AUTOMATIC FAIL SAFE OPEN ON POWER LOSS (CAN BE PROGRAMMED FOR OTHER OPTIONS)

PORTS FOR PLUG-IN LOOP DETECTORS (OPEN, REVERSE, SHADOW)

PERFORMANCE

SL-C-CD:

40' opening 1,700lb gate

SL-I-CD:

50' opening 2,700lb gate

MISCELLANEOUS

SHIPPING WEIGHT: TWO BOXES APPROXIMATELY 45LBS (20.5KG)

OPERATOR REQUIRES MONITORED TYPE B1 AND/OR TYPE B2 ENTRAPMENT PROTECTION DEVICES

ROTARY IQ AVAILABLE FOR REMOTE MONITORING, PROGRAMMING, AND CUSTOMER ACCESS CONTROL.